



FP ATF CVT SYNTHETIC

PRODUCT DESCRIPTION:

FP ATF CVT is a fully synthetic premium multi-vehicle transmission fluid for passenger cars and vans. A well-balanced fluid that provides exceptional metal-to-metal frictional properties to help prevent belt and chain slipping and help extend transmission life. It provides superior wet-clutch performance for outstanding anti-shudder durability and reduced noise, vibration and harshness.

APPLICATION:

Especially recommended for use in push belt and chain-driven continuously variable transmissions of most European, Asian, and American passenger cars and vans.

FEATURES & BENEFITS:

- Exceptional steel on steel friction durability maintains transmission performance.
- Good gear wear protection prolongs the performance and life of the transmission.
- High shear stability and enhanced anti foaming and air release characteristics maintain effective lubrication.
- Superior wet-clutch performance for outstanding anti-shudder durability and reduced noise, vibration and harshness.
- In elevated heat, guards against the harmful effects of thermal breakdown.

PERFORMANCE LEVELS: Meets or Exceeds:

Mazda CVTF 3320 • MB 236.2 • Nissan NS-1, NS-2, NS-3 • Toyota/Lexus TC, FE • Ford CVT23, CVT30, WSS-M2C933-A • Mitsubishi DiaQueen CVTF-J1/CVTF-J4/SP-III • Audi/VW TL 52180, G 052 180, G 052 516 • Suzuki CVTF 3320, TC, NS-2, CVTF Green1, CVTF Green 2 • Honda HMMF / HCF-2 / Z1 • AUDI MULTITRONIC • BMW MINI COOPER EZL799/799A/ZF CVT V1 • DAIHATSU AMMIX DC/DFC/CVTF-DFE • DAIHATSU TC • CHRYSLER/DODGE/JEEP NS-2/CVT +4 • GM DEX-CVT • HYUNDAI/KIA CVT-J1 / SP-III • IDEMITSU CVTS-EX1 • VAG TL 521 16 (G052 516) / TL 521 80 (G 052 180 A2) • PUNCH CVT • SHELL GREEN 1V • SUBARU ECVT / iCVT / iCVT FG / NS2 / LINEARTRONIC CVT CHAIN / LINEARTRONIC CVT II / HIGH TORQUE LINEARTRONIC

TYPICAL PROPERTIES:

PARAMETERS	ASTM	UNIT	RESULT
Grade			CVT
Kinematic Viscosity@ 104°F / 40°C	ASTM D7042	cSt	34.0
Kinematic Viscosity@ 212°F / 100°C	ASTM D7042	cSt	7.0
Viscosity Index	ASTM D2270	-	173
SP. Gravity @15°C/60°F	ASTM D4052	g/cm ³	0.848
Flash Point	ASTM D92	°C	220
Pour Point	ASTM D97	°C	-45
Brookfield Viscosity @ -40 °C	ASTM D-2983	mPa.s (cP)	9000

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point.