



FP ATF DEXRON II SYNTHETIC

PRODUCT DESCRIPTION:

FP ATF DEXRON II is a Multi-functional Automatic Transmission Fluid (ATF) of the DEXRON IID generation. Its good performance capacity is achieved through the interaction of selected mineral base oils and special additives. For use in automatic transmissions, steering systems and hydraulics in passenger cars, commercial vehicles and construction machinery.

APPLICATION:

FP ATF DEXRON II is used in a variety of units according to the manufacturer's specification. It is thus used in manual and automatic transmissions, power steering systems, power-shift clutches as well as in power transmission fluid in many hydraulic applications.

FEATURES & BENEFITS:

- Very good economy grade for multi-functional use in many units.
- Improved friction coefficient stability.
- Excellent shifting characteristics at low temperatures.
- The best wear protection properties for reliable operation and the longest service life.
- Outstanding ageing and oxidation stability.
- Minimal tendency to foam.
- Reliable protection against corrosion, wear, sludge accumulation and adhesion.

PERFORMANCE LEVELS: Meets or Exceeds:

DEXRON IID, MERCON, Allison C-4, CAT TO-2, DTFR 13C100 (ex. MB 236.1), MAN 339 Type Z1/V1, MB 236.5, Voith 55.6335.xx (G607), ZF TE-ML 09, 11A, 14A, Ford M2C138-CJ/166-H, MB 236.6, Volvo 97335

TYPICAL PROPERTIES:

PARAMETERS	ASTM	UNIT	RESULT
Grade			ATF DEXRON II
Kinematic Viscosity@ 104°F /40°C	ASTM D7042	cSt	38.0
Kinematic Viscosity@ 212°F /100°C	ASTM D7042	cSt	7.5
Viscosity Index	ASTM D2270	-	180
SP. Gravity @15°C/60°F	ASTM D4052	g/cm ³	0.856
Flash Point	ASTM D92	°C	220
Pour Point	ASTM D97	°C	-42

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point.