



## **FP ATF DEXRON IIIH SYNTHETIC**

### **PRODUCT DESCRIPTION:**

FP ATF DEXRON IIIH is a high-performance ATF with an extremely wide range of applications in modern 'stepped' automatic transmissions. Its exceptional performance capacity is achieved through the interaction of the most advanced additives and specially selected HC synthetic oils.

### **APPLICATION:**

FP ATF DEXRON IIIH is a multi-functional ATF that combines the requirements of the most common specifications from American, European and Japanese manufacturers.

### **FEATURES & BENEFITS:**

- Outstanding ATF economy grade
- Excellent shifting characteristics at low temperatures
- The best wear protection properties for reliable operation and the longest service life
- Outstanding ageing and oxidation stability
- Minimal tendency to foam
- Reliable protection against corrosion, wear, sludge accumulation and adhesion

### **PERFORMANCE LEVELS: Meets or Exceeds:**

DEXRON IIIH, MERCON/MERCON V, Allison C-4, MB 236.6, ZF TE-ML 16L, 16R, 17C, DTFR 13C170 (ex. MB 236.9), MAN 339 Type V1/Z11/Z2, Voith 55.6335.xx (G607), ZF TE-ML 04D, 14B, 20B, 25B, Chrysler ATF+3/+4, GM 9986195, Honda Z1, Hyundai/Kia/Mitsubishi SP-II-III, Nissan Matic-D/J/K, Toyota T-IV/JWS 3309, Volvo 97341/Volvo 5-Speed (1161540), VW 50 160/TL 52 162/G 052 990/G 055 025

### **TYPICAL PROPERTIES:**

PARAMETERS	ASTM	UNIT	RESULT
Grade			ATF DEXRON IIIH
Kinematic Viscosity@ 104°F /40°C	ASTM D7042	cSt	34.0
Kinematic Viscosity@ 212°F /100°C	ASTM D7042	cSt	7.2
Viscosity Index	ASTM D2270	-	185
SP. Gravity @15°C/60°F	ASTM D4052	g/cm <sup>3</sup>	0.854
Flash Point	ASTM D92	°C	222
Pour Point	ASTM D97	°C	-42

### **HEALTH & SAFETY, ENVIRONMENT:**

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point.