



## **FP ATF TYPE A SYNTHETIC**

### **PRODUCT DESCRIPTION:**

FP ATF TYPE A is an automatic transmission fluid developed for the automatic transmissions and power steering systems of vehicles specifying use of General Motors TYPE A SUFFIX A quality fluids. The highly refined base oils and proven performance additives used in this oil provide enhanced thermal stability, frictional characteristics and rust & corrosion protection. It exceeds the performance requirements of General Motors TYPE A SUFFIX A specification.

### **APPLICATION:**

FP ATF TYPE A is recommended for automatic transmissions and power steering systems of vehicles requiring General Motors TYPE A SUFFIX A quality fluids. It is also recommended for certain manual transmissions and hydraulic systems where such type of fluids are specified.

### **FEATURES & BENEFITS:**

- Excellent oxidation stability
- High viscosity index
- Corrosion prevention
- Smoothens transmission process
- Foaming resistance
- Controlled friction properties.

### **PERFORMANCE LEVELS: Meets or Exceeds:**

- GM Type A Suffix A
- MB 236.2

### **TYPICAL PROPERTIES:**

PARAMETERS	ASTM	UNIT	RESULT
Grade			ATF Type A
Kinematic Viscosity@ 104°F /40°C	ASTM D7042	cSt	41.3
Kinematic Viscosity@ 212°F /100°C	ASTM D7042	cSt	7.6
Viscosity Index	ASTM D2270	-	155
SP. Gravity @15°C/60°F	ASTM D4052	g/cm <sup>3</sup>	0.872
Flash Point	ASTM D92	°C	208
Pour Point	ASTM D97	°C	-39

### **HEALTH & SAFETY, ENVIRONMENT:**

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point.