



FP ATF ZF 8 SPEED

AUTOMATIC TRANSMISSION FLUID

PRODUCT DESCRIPTION:

FP ATF ZF 8 SPEED is an Automatic Transmission Fluid (ATF) suitable for a large variety of applications. It is formulated from selected synthetic base oils and special additives which guarantees a perfect function of the automatic transmission and offers safe operation even under high stress.

APPLICATION:

FP ATF ZF 8 SPEED is suitable for use in automatic ZF transmission of 8HP-Series 8HP45, 8HP55, 6HP26, 8HP70, 8HP90, also for ZF transmission 6-stroke automatic 6HP-series - 6HP19X for AUDI Q7, 6HP19A, 6HP28AF. It can also be used in ZF transmission series 9HP48.

FEATURES & BENEFITS:

- Reduced vibration.
- Improved lubricating
- Reduced wear and softer shifting operations due to consistent friction behavior
- Increased sound dampening due to low viscosity.
- maximum reduction of fuel consumption, which reduces emission

PERFORMANCE LEVELS: Meets or Exceeds:

ZF Lifeguard 8 • Audi / VW Oil No. G 060162 A1 / A2 / A6 • Jaguar Oil No. 02JDE 26444 • Land Rover Oil No. LR023288 • Chrysler Oil No. 68157995AA • Petronas Tutela Transmission AS8 • BMW 83 222 152 426 • BMW 83 222 305 397 (ATF3) • BMW 83 222 289 720 (ATF3+) • Fiat 9.55550-AV5 • Bentley JNV 862 564 D

TYPICAL PROPERTIES:

PARAMETERS	ASTM	UNIT	RESULT
Grade			ATF ZF 8 SPEED
Kinematic Viscosity@ 104°F / 40°C	ASTM D7042	cSt	30.5
Kinematic Viscosity@ 212°F / 100°C	ASTM D7042	cSt	6.1
Viscosity Index	ASTM D2270	-	151
SP. Gravity @15°C/60°F	ASTM D4052	g/cm ³	0.848
Flash Point	ASTM D92	°C	216
Pour Point	ASTM D97	°C	-42

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point.