



FP MARINEÖL PRE-MIX 2T

PRODUCT DESCRIPTION:

FP MARINEÖL PRE-MIX 2T is low ash high performance 2 stroke engine oil, pre-diluted to facilitate mixing when added to fuel. It is formulated with high quality mineral & synthesized baseoils and advanced technology additive system to provide reliable performance in direct injection and pre-mix engines. It is suitable for use in naturally aspirated 2 stroke engines such as lawnmowers, chainsaws, motorcycles and auxiliary equipment.

FEATURES & BENEFITS:

- Outstanding oxidation & thermal stability reduces sludge build up and keeps the engine cleaner, resulting in extended spark plug and valve life, reduced ring sticking, piston tightening and prevention of pre-ignition problems
- Excellent engine protection by providing outstanding protection against wear.
- Excellent corrosion protection helps enhancing engine life.
- Low smoke exhaust resulting in cleaner environment.

PERFORMANCE LEVELS: Meets or Exceeds:

- API TC
- JASO FB, FC, FD
- ISO L-EGD

TYPICAL PROPERTIES:

PARAMETERS	ASTM	UNIT	RESULT
Grade			PRE MIX 2T
Kinematic Viscosity@ 104°F /40°C	ASTM D7042	cSt	47.15
Kinematic Viscosity@ 212°F /100°C	ASTM D7042	cSt	7.8
Viscosity Index	ASTM D2270	-	135
SP. Gravity @15°C/60°F	ASTM D4052	g/cm ³	0.866
Flash Point	ASTM D92	°C	96
Pour Point	ASTM D97	°C	-24

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point.