



FP MOTORÖL LS C2 0W-30

FULLY SYNTHETIC

PRODUCT DESCRIPTION:

FP MOTORÖL LS C2 is fully synthetic fuel economy engine oil formulated for use in modern engines requiring low friction, low HTHS viscosity and Mid SAPS oil. The high-quality base oils in combination with our most up-to-date additive technology ensures excellent aging stability, optimum wear protection, fuel savings and outstanding cold start properties over the entire oil change interval. FP MOTORÖL LS C2 meets the requirements of Euro VI emission regulations.

APPLICATION:

FP MOTORÖL LS C2 is Recommended for diesel and petrol powered engines of FORD, JAGUAR, LAND ROVER, CHRYSLER and FIAT where ACEA C2 class fluid with SAE 0W-30 viscosity grade is recommended.

FEATURES & BENEFITS:

- Keeps engine clean by minimizing deposits.
- Optimized for emission control systems.
- Excellent cold start performance.
- Provides ultimate protection against wear under all operating conditions including start-start operation.
- Minimizes oil hydrodynamic friction, allowing fuel economy especially when oil is cold.

PERFORMANCE LEVELS: Meets or Exceeds:

SAE	0W-30
ACEA-22	C2
API	SN/CF
FORD	WSS M2C 950A
JAGUAR LAND ROVER	STJLR.03.5007
CHRYSLER	MS-13340/ MS-90047
FIAT	9.55535-GS1/DS1
PSA	-
RENAULT	RN0700

TYPICAL PROPERTIES:

PARAMETERS	ASTM	UNIT	RESULT
Grade			0W-30
Kinematic Viscosity@ 104°F /40°C	ASTM D7042	cSt	55.6
Kinematic Viscosity@ 212°F /100°C	ASTM D7042	cSt	10.2
Viscosity Index	ASTM D2270	-	174
SP. Gravity @15°C/60°F	ASTM D4052	g/cm ³	0.842
Flash Point	ASTM D92	°C	214
Pour Point	ASTM D97	°C	-45
TBN	ASTM D2896	mg KOH/g	8.0
CCS, (°C)	ASTM D5293	m.Pa.S	<6200(-35°C)

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point.