



FP MOTORÖL LS 0W-30

FULLY SYNTHETIC

PRODUCT DESCRIPTION:

FP MOTORÖL LS 0W-30 is a high quality fully synthetic engine oil engineered for the demands of modern engines, ensuring maximum protection against wear, corrosion, and sludge buildup. Ideal for vehicles equipped with advanced emission systems, this oil helps extend the life of critical components such as the Diesel Particulate Filter (DPF) and Three-Way Catalysts (TWC).

APPLICATION:

FP MOTORÖL LS 0W-30 Engine Oil is recommended for passenger cars, light trucks, gasoline powered equipment and hybrid engines. For all-season use in engines operating on gasoline, high-ethanol gasoline with and without turbo-charging and direct injection.

FEATURES & BENEFITS:

- Low viscosity, advanced full synthetic formula
- Outstanding low temperature capabilities.
- Can clean up sludge left behind in your engine.
- Incorporate low ash foaming additive to extend DPF (Diesel Particulate Filters) service lifetime.
- Low Sulphur and Phosphorous content help to reduce poisoning of Gasoline Catalytic Converters (CAT's).
- Sustains maximum performance even when under pressure.
- Reduces engine deposits to help maximize engine response

PERFORMANCE LEVELS: Meets or Exceeds:

API SN/CF, ACEA C2/C3, VW 504.00/507.00, MB 229.31, MB 229.51/229.52, RN 0700/0710, BMW LL-04, CHRYSLER MS-11106, FIAT 9.55535-DS1/GS1, Porsche C30, FORD WSS-M2C90-A, PSA B71 2390 / B71 2312

TYPICAL PROPERTIES:

PARAMETERS	ASTM	UNIT	RESULT
Grade			0W-30
Kinematic Viscosity@ 104°F /40°C	ASTM D7042	cSt	64.5
Kinematic Viscosity@ 212°F /100°C	ASTM D7042	cSt	11.5
Viscosity Index(min)	ASTM D2270	-	175
SP. Gravity @15°C/60°F	ASTM D4052	g/cm ³	0.842
Flash Point (min)	ASTM D92	°C	220
Pour Point (max)	ASTM D97	°C	-45
TBN	ASTM D2896	mg KOH/g	7.4
CCS, (°C)	ASTM D5293	m.Pa.S	<6200(-35°C)

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point.