



## **FP MOTORÖL LS VW 0W-20**

### **FULLY SYNTHETIC**

#### **PRODUCT DESCRIPTION:**

FP MOTORÖL LS VW 0W-20 is a high-performance synthetic lubricant developed for the latest Volkswagen (Audi, VW, Seat and Skoda) engines that need VW 508 00/509 00 approval. Suitable for use in petrol and diesel vehicles. This product provides superior protection against wear, rust and deposits. The low SAPS technology for Euro 6 exhausts offers ultimate protection for aftertreatment systems. It meets VW 508.00/509.00 and Porsche C20 specifications.

#### **APPLICATION:**

FP MOTORÖL LS VW 0W-20 was developed specifically for use in new VW gasoline and diesel engines and has been approved for engines that require an oil that is compatible with the specifications of VW 508 00/509 00. Although it delivers maximum rarefaction in terms of viscosity, it offers optimum wear and tear characteristics and performance reserves even in combination with extended oil change intervals.

#### **FEATURES & BENEFITS:**

- Improved fuel economy
- Exceptional engine performance in different driving conditions.
- Exceptional engine protection after cold starting.
- Extended drain interval capability
- Superior protection against rust and corrosion.

#### **PERFORMANCE LEVELS: Meets or Exceeds:**

- Porsche C20
- VW 508 00/509 00
- ACEA C5
- Ford WSS-M2C956-A1
- ACEA A1/B1

#### **TYPICAL PROPERTIES:**

PARAMETERS	ASTM	UNIT	RESULT
Grade			10W-40
Kinematic Viscosity@ 104°F /40°C	ASTM D7042	cSt	96
Kinematic Viscosity@ 212°F /100°C	ASTM D7042	cSt	14.4
Viscosity Index	ASTM D2270	-	155
SP. Gravity @15°C/60°F	ASTM D4052	g/cm <sup>3</sup>	0.875
Flash Point	ASTM D92	°C	228
Pour Point	ASTM D97	°C	-36
TBN	ASTM D2896	mg KOH/g	10.2
CCS, (°C)	ASTM D5293	m.Pa.S	<7000(-25°C)

#### **HEALTH & SAFETY, ENVIRONMENT:**

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point.