



FP MOTORÖL PSA SAE 0W-30 **FULLY SYNTHETIC**

PRODUCT DESCRIPTION:

FP MOTORÖL PSA SAE 0W-30 is a high-performance reduced SAPS formula specially designed for recent vehicles of PSA group (Peugeot and Citroën) equipped with diesel engines "Blue HDI" SCR (Selective Catalytic Reduction) requiring lubricant meeting B71 2312 specification. It also meets the requirements of EURO 4, EURO 5 and EURO 6 pollution control standards and maintains the efficiency of the car exhaust Emission Reduction Systems in both diesel and gasoline powered automobiles. Fully synthetic base provides excellent thermal stability and wear protection and it prevents the formation of varnish and sludge to preserve the engine cleanliness.

APPLICATION:

FP MOTORÖL PSA SAE 0W-30 is recommended for all Peugeot "Blue HDi" diesel engines and Citroën equipped with SCR systems. The B71 2312 specification also covers the specifications of the majority of gasoline engines and PSA - Peugeot Citroën HDi FAP Diesel engines.

FEATURES & BENEFITS:

- Low SAPS formulation helps to prolong the life and maintains the efficiency of the Emission Reduction Systems in both Diesel and Gasoline powered engines.
- Help achieve fuel economy.
- Improved cold flow properties
- Offers the best possible protection in its category against wear and clogging.
- Reduced environmental impact.

PERFORMANCE LEVELS: Meets or Exceeds:

SAE GRADE	0W-30	
ACEA-22	C2	
PSA	B71 2312	

TYPICAL PROPERTIES:

PARAMETERS	ASTM	UNIT	RESULT
Grade			0W-30
Kinematic Viscosity@ 104°F/40°C	ASTM D7042	cSt	64.5
Kinematic Viscosity@ 212°F/100°C	ASTM D7042	cSt	11.5
Viscosity Index	ASTM D2270	-	175
SP. Gravity @15°C/60°F	ASTM D4052	g/cm ³	0.842
Flash Point	ASTM D92	°C	220
Pour Point	ASTM D97	°C	-45
TBN	ASTM D2896	mg KOH/g	7.0
CCS, (°C)	ASTM D5293	m.Pa.S	<6200(-35°C)

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point.