



FP MOTORÖL RS 15W-40 MINERAL

PRODUCT DESCRIPTION:

FP MOTORÖL RS 15W-40 is an advanced performance engine oil for passenger cars and light duty commercial vehicles. This lubricant ensures optimum engine protection, keeps the engine clean and prevents sludge formation. The product meets ACEA A3/B4 requirements.

APPLICATION:

FP MOTORÖL RS 15W- 40 is recommended for passenger cars and vans with gasoline or LPG engines. It is suitable for engines with a catalyst and normally aspirated as well as turbocharged diesel engines. The product meets ACEA A3/B4 requirements.

FEATURES & BENEFITS:

- Optimal wear prevention ensuring long engine life.
- High engine cleanliness increasing engine durability.
- Premium protection against rust and corrosion.
- Stable lubricating film, even with hot oil and under excessive loads
- High level of oxidation protection by means of selected base oils and special additives
- Very low oil consumption

PERFORMANCE LEVELS: Meets or Exceeds:

- ACEA A3/B4
- API SN/CF
- VW 501 01/505 00
- Fiat 9.55535-G2/D2
- MB 229.1

TYPICAL PROPERTIES:

PARAMETERS	ASTM	UNIT	RESULT
Grade			15W-40
Kinematic Viscosity@ 104°F /40°C	ASTM D7042	cSt	120
Kinematic Viscosity@ 212°F /100°C	ASTM D7042	cSt	15.4
Viscosity Index	ASTM D2270	-	134
SP. Gravity @15°C/60°F	ASTM D4052	g/cm ³	0.875
Flash Point	ASTM D92	°C	236
Pour Point	ASTM D97	°C	-33
TBN	ASTM D2896	mg KOH/g	10.2
CCS, (°C)	ASTM D5293	m.Pa.S	<7000 (-20°C)

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point.