



FP MOTORÖL RS 20W-50

FULLY SYNTHETIC

PRODUCT DESCRIPTION:

FP MOTORÖL RS 20W-50 is formulated from quality base stocks combined with modern performance additives to give your engine the protection and the performance you expect under a wide variety of operating conditions. This oil is designed to provide improved oxidation resistance, improved deposit protection, better wear protection, and better low temperature performance over the life of the oil.

APPLICATION:

FP MOTORÖL RS 20W-50 Recommended for naturally aspirated and turbo-charged gasoline engines in passenger cars and light commercial vehicles, four-stroke gasoline engines and portable power equipment.

FEATURES & BENEFITS:

- "Viscous" formula well-suited to long stays in hot countries (20W for example)
- Particularly recommended for urban driving
- Resistant to extreme thermal load due to high quality of base oil.
- Protects engines against deposits
- Standard drain interval

PERFORMANCE LEVELS: Meets or Exceeds:

- API SM/CF
- ACEA A3/B3
- VW 501 01/505 00
- RN 700, RN 710

TYPICAL PROPERTIES:

PARAMETERS	ASTM	UNIT	RESULT
Grade			20W-50
Kinematic Viscosity@ 104°F /40°C	ASTM D7042	cSt	160
Kinematic Viscosity@ 212°F /100°C	ASTM D7042	cSt	18.5
Viscosity Index	ASTM D2270	-	130
SP. Gravity @15°C/60°F	ASTM D4052	g/cm ³	0.892
Flash Point	ASTM D92	°C	242
Pour Point	ASTM D97	°C	-30
TBN	ASTM D2896	mg KOH/g	8.5
CCS, (°C)	ASTM D5293	m.Pa.S	<9500(-15°C)

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point.