



FP MOTORÖL SPEZIAL 15W-40 MINERAL

PRODUCT DESCRIPTION:

FP MOTORÖL SPEZIAL 15W-40 is designed to be used for passenger cars, light trucks as well as farm equipment, especially where single type of oil is preferred. This oil contains inhibitors to combat acids formation, oxidation and foaming. It is formulated with high quality mineral base stock and advance additive system.

APPLICATION:

Gasoline and light-duty diesel engines found in passenger cars, farm and construction equipment, stationary diesel engines and four stroke engines.

FEATURES & BENEFITS:

- Superior viscosity retention
- Oxidation resistant
- Wear and friction protection
- Engine Cleanliness and low combustion residue
- Excellent detergency and dispersancy

PERFORMANCE LEVELS: Meets or Exceeds:

- API SF/CD
- CCMC D2/G2
- MIL-L-2104D

TYPICAL PROPERTIES:

PARAMETERS	ASTM	UNIT	RESULT
Grade			15W-40
Kinematic Viscosity@ 104°F /40°C	ASTM D7042	cSt	120
Kinematic Viscosity@ 212°F /100°C	ASTM D7042	cSt	15.4
Viscosity Index	ASTM D2270	-	134
SP. Gravity @15°C/60°F	ASTM D4052	g/cm ³	0.875
Flash Point	ASTM D92	°C	236
Pour Point	ASTM D97	°C	-33
TBN	ASTM D2896	mg KOH/g	6.0
CCS, (°C)	ASTM D5293	m.Pa.S	<7000 (-20°C)

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point.