



FP MOTORRADÖL 2T

2 STROKE ENGINE OIL

PRODUCT DESCRIPTION:

FP MOTORRADÖL 2T is a lubricant which is designed to provide excellent performance in two-stroke engines like motorcycles, scooters and mopeds. Its composition is perfectly compatible with lead free fuels. This is a high technology product combining a perfect balance of highly refined base stocks and the latest additives technology. It is specially formulated for use in oil injected as well as premixed gasoline/oil lubricated engines. Its increased performance provides protection against exhaust emissions and engine carbon deposits.

APPLICATION:

FP MOTORRADÖL 2T is intended for use in two-stroke air cooled engines. Also suitable for motorcycles, scooters, mopeds, snow mobiles, lawn mowers, golf carts, chain saws and other two-stroke powered applications where API TC lubricants are recommended. Product is to be used as per OEM recommended fuel/oil mix ratio. If the specific ratio is not provided, the general recommendation is to use 50:1 fuel/oil mix.

FEATURES & BENEFITS:

- Provides piston scuffing protection and reduces smoke.
- Thermal and oxidation stability.
- Specially formulated to avoid spark plug fouling.
- Perfectly adapted to unleaded fuel.
- Protection against pre-ignition problems.

PERFORMANCE LEVELS: Meets or Exceeds:

- API TC
- JASO FB, FC, FD
- ISO L-EGD

TYPICAL PROPERTIES:

PARAMETERS	ASTM	UNIT	RESULT
Grade			2T
Kinematic Viscosity@ 104°F /40°C	ASTM D7042	cSt	62.6
Kinematic Viscosity@ 212°F /100°C	ASTM D7042	cSt	9.0
Viscosity Index	ASTM D2270	-	120
SP. Gravity @15°C/60°F	ASTM D4052	g/cm ³	0.884
Flash Point	ASTM D92	°C	224
Pour Point	ASTM D97	°C	-24

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point.