



FP MOTORRADÖL 4T 10W-60

FULLY SYNTHETIC

PRODUCT DESCRIPTION:

FP MOTORRADÖL 4T 10W-60 is a fully synthetic lubricant developed for race bikes fitted with high performance four-stroke engines. It is blended by using synthetic Ester base stocks with low traction coefficient and a precisely balanced additive system to help provide maximum power output and engine cleanliness. Rave 4T provides shear stable lubricant film which helps reduce engine wear and offers unsurpassed gear box protection under severe operating conditions in all seasons, driving environments and on the race track.

APPLICATION:

FP MOTORRADÖL 4T 10W-60 is recommended for race bikes fitted with integrated gear box or not, wet or dry clutch, speed bikes, MotoGP, Super Sport, Uphill, Dirt bikes, Enduro as well as ATVs and UTVs.

FEATURES & BENEFITS:

- Maximum engine power.
- Unsurpassed gear protection.
- Outstanding wear protection.
- Excellent shear and oxidation resistance.
- Excellent low temperature fluidity.

PERFORMANCE LEVELS: Meets or Exceeds:

- API SN
- JASO MA2

TYPICAL PROPERTIES:

PARAMETERS	ASTM	UNIT	RESULT
Grade			10W-60
Kinematic Viscosity@ 104°F /40°C	ASTM D7042	cSt	189.7
Kinematic Viscosity@ 212°F /100°C	ASTM D7042	cSt	24
Viscosity Index	ASTM D2270	-	156
SP. Gravity @15°C/60°F	ASTM D4052	g/cm ³	0.854
Flash Point	ASTM D92	°C	232
Pour Point	ASTM D97	°C	-33

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point.