



FP MOTORRADÖL 4T 20W-50

MINERAL

PRODUCT DESCRIPTION:

FP MOTORRADÖL 4T is a high quality engine oil designed for 4-stroke motorcycles. It is based on premium quality base oils and advanced additives to bring out the best in your machine. It is designed to ensure maximum power and performance, even under the most demanding riding conditions. Its anti-friction formulation is proven to increase acceleration compared to conventional motorcycle oils. it protects the engine, clutch, gears and allows the best functionality of these three critical areas of the motorcycle.

APPLICATION:

FP MOTORRADÖL 4T is Recommended for all 4-Stroke motorcycles including cruisers and off-road motorcycles.

FEATURES & BENEFITS:

- Excellent shear stability.
- Provides high temperature protection.
- · Outstanding wet clutch protection for maximum power transfer and smooth shifting.
- Excellent wear and corrosion protection.
- Maximizes power and acceleration.
- Added protection against harmful deposits.

PERFORMANCE LEVELS: Meets or Exceeds:

- API SL
- JASO MA2

TYPICAL PROPERTIES:

| PARAMETERS | ASTM | UNIT | RESULT |
|-----------------------------------|------------|-------------------|--------------|
| Grade | | | 20W-50 |
| Kinematic Viscosity@104°F/40°C | ASTM D7042 | cSt | 173 |
| Kinematic Viscosity@ 212°F /100°C | ASTM D7042 | cSt | 20.4 |
| Viscosity Index | ASTM D2270 | - | 137 |
| SP. Gravity @15°C/60°F | ASTM D4052 | g/cm ³ | 0.890 |
| Flash Point | ASTM D92 | °C | 236 |
| Pour Point | ASTM D97 | °C | -24 |
| TBN | ASTM D2896 | mg KOH/g | 7.0 |
| CCS, (°C) | ASTM D5293 | m.Pa.S | <9500(-15°C) |

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point.