



FP SCHMIERFELL L-EP NLGI 2

MULTI-PURPOSE EXTREME PRESSURE LITHIUM GREASE

PRODUCT DESCRIPTION:

FP SCHMIERFELL L-EP Greases are premium quality lithium soap-thickened lubricating greases formulated with refined mineral base oils and fortified with Extreme Pressure (EP) additives. They are designed to provide reliable lubrication and protection in a wide range of applications, including heavy-duty and shock-load conditions. Their smooth texture and excellent mechanical stability ensure easy handling and superior pumpability, even in centralized lubrication systems.

APPLICATION:

FP SCHMIERFELL Lithium – EP-2 is recommended for multipurpose applications in antifriction and plain bearings, bushings and pins under normal operating conditions.

FEATURES & BENEFITS:

- Outstanding wear protection under heavy/shock loads
- Effective rust and corrosion resistance
- Excellent resistance to water washout
- Enhanced mechanical stability and oxidation resistance
- Good pumpability for centralized lubrication systems
- Leakage control in high-speed applications
- Extended service life for bearings and components

PERFORMANCE LEVELS: Meets or Exceeds:

- NLGI Grade: 2
- NLGI Grade: 3

MEETS OR EXCEEDS THE REQUIREMENTS OF:	NLGI 2
DIN 51825	KP2K-20
DIN 51826	-

TYPICAL PROPERTIES:

PARAMETERS	ASTM METHOD	FP SCHMIERFELL L-EP NLGI 2
Thickener Type	-	Lithium
Color	-	Light Brown
Texture	-	Smooth
Worked Penetration @ 25°C, 60 Strokes	D-217	280
Dropping Point, °C	D-2265	190
Timken EP Test, OK Load, lbs	D-2509	40
4-Ball Wear, Scar, mm	D-2266	0.4
4-Ball Weld Load, Kg	D-2596	250
Base Oil Viscosity @ 40°C, cSt	D-445	160
Operating Temperature Range, °C	-	-30 to 130

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point.