



FP SCHMIERFELL L-MP NLGI 2

HIGH-PERFORMANCE MULTI-PURPOSE LITHIUM GREASE

PRODUCT DESCRIPTION:

FP SCHMIERFELL L-MP Greases is multipurpose grease for general lubrication under normal operating conditions and loads, formulated for lubrication of all kinds of universal applications in transport, agriculture and off road equipment operating in wet, dusty and/or dry conditions.

APPLICATION:

FP SCHMIERFELL L-MP is used for lubrication of all kinds of bearings and joints when the temperature and loading conditions are normal. Pre-eminently suitable for passenger car, light truck and leisure vehicle applications. Always avoid contamination of the grease by dust and/or dirt when applying.

FEATURES & BENEFITS:

- Excellent mechanical stability avoiding ejection or loss of consistency during operation.
- Excellent pumpability due to the low temperature characteristics and smooth texture.
- Very good water resistance, even in a humid environment a sufficient lubricating film will be maintained.

PERFORMANCE LEVELS: Meets or Exceeds:

- NLGI Grade: 2
- NLGI Grade: 3

TYPICAL PROPERTIES:

PARAMETERS	ASTM METHOD	FP SCHMIERFELL L-MP NLGI 2
Thickener Type	-	Lithium
Color	-	Light Brown
Texture	-	Smooth
Worked Penetration @ 25°C, 60 Strokes	D-217	280
Dropping Point, °C	D-2265	190
Base Oil Viscosity @ 40°C, cSt	D-445	150
Operating Temperature Range, °C	-	-25 to 120

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point.