



FP TRAKTORÖL STOU 10W-30

SEMI SYNTHETIC/MINERAL

PRODUCT DESCRIPTION:

FP TRAKTORÖL STOU 10W-30 is a premium multi-functional oil especially formulated for use in agricultural equipment, engines, transmissions, and differentials with wet brake system and integrated hydraulic system. The carefully chosen base oils and additive system forms a thermal and oxidation stable oil film thus keeps the engine, gear box, differential, and hydraulic system clean and in good condition.

FEATURES & BENEFITS:

- It has anti-wear and EP (extreme pressure) properties that protect the bearings and gear teeth against wear.
- High pressure-absorption capability.
- Stable to oxidation.
- High resistance to aging.
- Universal application.
- High wear resistance.
- Good cold start behavior.

PERFORMANCE LEVELS: Meets or Exceeds:

API: CG-4 / GL-4, ZF TE-ML 06A, B, C, R, 07B, FORD M2C 159B, C, FORD NH 82009201, 2, 3, FORD M2C 86B, C, 134D, MASSEY FERGUSON M1145, M1139, M1144, JOHN DEERE JDM J27, J20C, J20D, ALLISON C4, Suitable for Wet Bakes

TYPICAL PROPERTIES:

PARAMETERS	ASTM	UNIT	RESULT
Grade			10W-30
Kinematic Viscosity@ 104°F / 40°C	ASTM D7042	cSt	62.6
Kinematic Viscosity@ 212°F / 100°C	ASTM D7042	cSt	10.4
Viscosity Index	ASTM D2270	-	155
SP. Gravity @15°C/60°F	ASTM D4052	g/cm ³	0.868
Flash Point	ASTM D92	°C	218
Pour Point	ASTM D97	°C	-36

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point.