



FP TRAKTORÖL STOU 15W-40

SEMI SYNTHETIC/MINERAL

PRODUCT DESCRIPTION:

FP TRAKTORÖL STOU 15W-40 is a multigrade universal and multifunction lubricating oil for tractors. Its carefully prepared formula is designed for use in internal combustion engines (including turbo engines), as well as transmissions, wet brakes, clutches and in hydraulic agricultural machinery systems. Lubricating oil for multiple services and general use.

FEATURES & BENEFITS:

- Excellent transmission lubrication.
- Outstanding hydraulic fluid properties.
- Limits wet brake noise while limiting friction plate wear.
- Excellent response of hydraulic components.
- Anti-wearing capacity to prevent scratches and wearing on gears.
- Excellent anti-noise properties on wet brakes.

PERFORMANCE LEVELS: Meets or Exceeds:

API CF-4/SF, JOHN DEERE J-27, ACEA E2, API GL-4, MB 228.1, 227.1, ALLISON C-4, MASSEY FERGUSON M-1145, CATERPILLAR TO-2, FORD M2C 159B, ZF TE-ML 06B/06C/07B, FENDT-VARIO

TYPICAL PROPERTIES:

PARAMETERS	ASTM	UNIT	RESULT
Grade			15W-40
Kinematic Viscosity@ 104°F /40°C	ASTM D7042	cSt	112
Kinematic Viscosity@ 212°F /100°C	ASTM D7042	cSt	15.2
Viscosity Index	ASTM D2270	-	142
SP. Gravity @15°C/60°F	ASTM D4052	g/cm ³	0.884
Flash Point	ASTM D92	°C	230
Pour Point	ASTM D97	°C	-30

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point.