



FP TRAKTORÖL UTTO 15W-30

SEMI SYNTHETIC/MINERAL

PRODUCT DESCRIPTION:

FP TRAKTORÖL UTTO is an extra high-performance multipurpose tractor lubricant engineered to meet or exceed transmission and hydraulic fluid requirements. It is particularly well suited for reducing wet brake and Power Take-Off (PTO) chatter. It helps protect against wear and corrosion of tractor components and has excellent anti friction properties. It optimizes the performance of agricultural and commercial tractors operating in a wide range of environments and conditions.

FEATURES & BENEFITS:

- It has anti-wear and EP (extreme pressure) properties that protect the bearings and gear teeth against wear.
- High pressure-absorption capability.
- Stable to oxidation.
- High resistance to aging.
- Universal application.
- High wear resistance.
- Good cold start behavior.

PERFORMANCE LEVELS: Meets or Exceeds:

API GL-4, ALLISON C4, Case MS 1204,6,7,9, Caterpillar TO-2, Ford / New Holland FNHA-2-C-201.00, Ford M2C-48B/C, Ford M2C-159A, Ford M2C-86B/C, Ford M2C-134 A/B/C/D, New Holland NH 410B, John Deere J20 A/B/C, J14 B/C, Massey Ferguson M1135, M1141, M1143, M 1145, ZF TE-ML-03E, 05F, 06K

TYPICAL PROPERTIES:

PARAMETERS	ASTM	UNIT	RESULT
Grade			15W-30
Kinematic Viscosity@ 104°F /40°C	ASTM D7042	cSt	65.6
Kinematic Viscosity@ 212°F /100°C	ASTM D7042	cSt	10.9
Viscosity Index	ASTM D2270	-	140
SP. Gravity @15°C/60°F	ASTM D4052	g/cm ³	0.880
Flash Point	ASTM D92	°C	230
Pour Point	ASTM D97	°C	-30

HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point.